CROMAUTO

TECHNICAL DATA SHEET



CRPROMP1 PLASTIC PROMOTER



Adhesion promotor for a wide variety of plastics in the automotive sector and motorcycle.

PRODUCTS

CRPROMP1 ADHESION PROMOTOR FOR PLASTICS

PROPERTIES

- Adhesion promotor applied to PUR, PS, PA, EPDM, ABS, PVC, GRP.
- Suitable for spots and small surfaces.
- Very easy application (Ready to use).

SUBSTRATES

- Very important: Remove dirt with soap and water.
- Remove grease with solvent CRD 05 ó CRD AQUA depending on the plastic. It is recommended to heat the work piece to prevent any release agent residue to appear on surface.
- If needed sand with P600 and remove any dust.
- Apply CROMAQUA O CROMACRYL over area.

8888			_	_
****	_	_	_	_

CROMAUTO

CRPROMP1 PLASTIC PROMOTER



PRODUCT PREPARATION

	Horizontal panel or mid size reparations										
	Ready to use.										
MIXING RATIO Volume											
VOC	654G/L										
POT-LIFE AT 20°C	N/A										
VISCOSITY APPLICATION AT 20°C	DIN 4 12-14										
*	GUN HLVP	Nozzle	Distance	Pressure							
APPLICATION EQUIPMENT	GRAVITY	1,31,5 mm.	10-15 cm.	1,82.2 bars							
NR DE MANOS	2 coats										
<u>{**{*{</u>	2 min. between layers.										
THINNER EVAPORATION											
DFT	2-4 microns										
DRYING TIME	DRY 5 min										



CRPROMP1 PLASTIC PROMOTER



SURFACE PREPARATION

- Wash the surface with soap and water. Rinse and dry.
- Remove grease thoroughly with proper cleanser. Dry surface with a clean cloth.
- Repair damages.
- Degrease using proper cleansing product. Dry with clean cloth.

STORAGE

Store products under cover, in a well-ventilated area, away from direct sun-light. Store at a temperature between 5- 30 degrees Celsius.

Duration of container at least 2 years. After that period, please consult our technical department.

CLEANING OF EQUIPMENT

Use a correct solventborne gunwash.

HEALTH AND SAFETY

For Professional use Only.

KEEP AWAY FROM CHILDREN. WARNING! FLAMMABLE CONTENT.

HARMFUL VAPORS AND VOLATILE COMPOUNDS. IRRITATING TO EYES AND SKIN.

Handle CROMAUTO products only after having read and understood completely the materials security and safety information sheets. Make sure that every employee is aware of data information sheets as well as all the chemical substances they get in contact with. The Manufacturer recommends the use of an air respirator while being exposed to the sprayed mist and vapors. Use appropriate clothing, gloves, and goggles with side shields.

The information provided in these sheets is given in good faith, but it is not guarantee constituent. The included information represents our current knowledge and it is aimed to serve as a guide or reference of our products and their purpose, but it does not guarantee certain properties of the products nor their specific applications.

Please, Observe the precautionary notices displayed on the container.